

January 29, 2024

Josh Hubbard Land Development Manager, Florida-East Toll Brothers 951 Broken Sound Parkway NW, Suite 180 Boca Raton, FL 33487

RE: Delray 36: TPS Traffic Statement Delray Beach, Florida

Delray 36 is a proposed residential development located on the west side of Sutton Place, south of Sherwood Boulevard in Delray Beach, Florida. The site currently contains vacant commercial uses but is not currently generating trips. The Applicant is proposing to redevelop the site with 27 single-family units. Access to the site is proposed via a full access connection to the west leg of Lakeview Boulevard & Sutton Place.

TRIP GENERATION

A trip generation comparison was conducted to evaluate the impacts associated with the proposed redevelopment. To conduct the analysis, trip generation rates and equations published by the Palm Beach County Traffic Division were used. *Table 1* summarizes the trip generation comparison between the existing uses and currently proposed programs of development on site. As shown in this table, the proposed change on the site is anticipated to result in an increase of 270 net new daily trips, an increase of 19 net new AM peak hour trips (+5 in, +14 out) and an increase of 25 net new PM peak hour trips (+16 in, +9 out). *Figure 1* illustrates the site location and trip assignment.

Because the proposed development program results in an increase in the existing traffic generated by this parcel on an AM and PM peak hour basis, the project's radius of development influence is 0.5 miles.


TRIP ASSIGNMENT

The site traffic was assigned to the surrounding roadway network based upon existing travel patterns and the traffic distribution. The AM and PM peak hour trips for the project were then assigned to the surrounding roadway network projected to be in place by 2029.



Table 1: Trip Generation Calculation

| Land Use | Int | ensity | Daily | F | AM Peak Ho | ur | | PM Peak Ho | our |
|-----------------------------|----------|----------|----------|------------------|------------|-----------|-----------------|------------|------|
| Lailu Ose | IIIC | Clisity | Trips | Total | In | Out | Total | In | Out |
| | | | Proposed | Scenario | | | | | |
| Single Family Detached | 27 | DU | 270 | 19 | 5 | 14 | 25 | 16 | 9 |
| | | Subtotal | 270 | 19 | 5 | 14 | 25 | 16 | 9 |
| Driveway Volumes | | | 270 | 19 | 5 | 14 | 25 | 16 | 9 |
| Net New External Trips | | | 270 | 19 | 5 | 14 | 25 | 16 | 9 |
| Radius of Development Influ | fluence: | | | 0.5 miles | | | | | |
| <u>Land Use</u> | | Daily | | AM Peak Ho | <u>ur</u> | PI | M Peak Hou | <u>r</u> | |
| Single Family Detached | 10 t | rips/DU | 0.7 tri | os/DU (26% in, 7 | 4% out) | 0.94 trip | s/DU (63% in, 3 | 7% out) | 0.0% |





Project Site

SITE LOCATION AND TRIP ASSIGNMENT DELRAY 36





ROADWAY IMPROVEMENTS

A review was conducted of the Five-Year Plans of Palm Beach County, as well as those improvements committed by the developers of projects in the area. No improvements were identified in the immediate vicinity of the site.

TEST 1 SIGNIFICANCE AND ROADWAY LINK ANALYSIS

A peak hour peak directional (PHPD) analysis was undertaken on the directly accessed links included in the Palm Beach County Thoroughfare Map to determine if these links are significantly impacted by the project traffic. Net new external project traffic was assigned to the directly accessed links per the project's radius of development influence. Per Palm Beach County standards, all the links on which the project impact is greater than 1% of the level of service (LOS) D generalized service volume are considered significantly impacted links.

As shown in *Tables 2a and 2b*, none of the roadway segments are significantly impacted. Therefore, no further analysis is required.

DRIVEWAY VOLUMES

Driveway Classification

Access to the site is proposed via a full access connection to the west leg of Lakeview Boulevard & Sutton Place. According to the Palm Beach County "Guide to Parking Lot and Street Access Design Criteria and Standards", it is necessary to classify project entrances that provide access to the local roadway network as minor, intermediate, or major according to the following criteria:

- Minor Services a maximum average daily volume of 500 vehicles.
- Intermediate Services a maximum average daily volume from 501 to 2,000 vehicles.
- Major Services a maximum average daily volume greater than 2,000 vehicles.

Using these criteria, the project driveway is classified as minor.

Turn Lane Requirements

Driveway volumes at the existing driveway connections have been evaluated in comparison with guidance provided in the Palm Beach County "Guide to Parking Lot and Street Access Design Criteria and Standards". According to the standards identified in this document, the volume thresholds for providing exclusive turn lanes are as follows:

Right-turn Lane – 75 peak hour right turns, with driveway volumes that exceed 1,000 trips per day, and average daily traffic volumes that exceed 10,000 vehicles per day.

Left-turn Lane – 30 peak hour left turns.

Based on the proposed driveway volumes, the turn lane thresholds are not exceeded.

Figure 2 illustrates the location and volumes for the site driveways.



Table 2a: AM Peak Hour Significance Analysis

| | | | COMMITTED | GSOT | | | PR | PRO JECT TRIPS | | | | |
|-------------|---------------|----------------|-----------|-----------|----------------|-------------|----|----------------|--------------|----------|------------|------|
| | | | NUMBER | GEN. SVC. | W FOR Odd | C. | | | AM PEAK HOUR | OUR | | |
| | | | OF | | ASSICNIARNT | NB/EB | | TRIPS | | % IMPACT | PACT . | |
| ROADWAY | FROM | TO | LANES | VOLUME | ASSIGINIVIEINI | : 100 / NII | _ | VB/EB SB/WB | NB/EB | Sig? | Sig? SB/WB | Sig? |
| | | | | | | | | | | | | |
| Military Tr | Atlantic Ave | Sherwood Blvd | G19 | 2,680 | 20% | 0 | 7 | 8 | 0.26% | No | 0.11% | No |
| Military Tr | Sherwood Blvd | Linton Blvd | G19 | 2,680 | 20% | - | 3 | 7 | 0.11% | No | 0.26% | No |
| Military Tr | Linton Blvd | Clint Moore Rd | G19 | 2,680 | 20% | - | - | 3 | 0.04% | No | 0.11% | No |
| | | | | | | | | | | | | |
| Linton Blvd | Sims Rd | Military Tr | 4ID | 1,770 | 15% | _ | - | 2 | %90.0 | 9 | 0.11% | 9 |
| Linton Blvd | Military Tr | Homewood Blvd | G19 | 2,680 | 15% | 0 | 2 | _ | 0.07% | 8 | 0.04% | 8 |



Table 2b: PM Peak Hour Significance Analysis

| | | | COMMITTED | TOSD | | | PR | PROJECT TRIPS | | | | |
|-------------|---------------|----------------|-----------|-----------|---------------|------------|-------|---------------|--------------|----------------|------------|------|
| | | | NUMBER | GEN. SVC. | i i | d i | | | PM PEAK HOUR | OUR | | |
| | | | OF | | PROJECT % | NB/EB | TR | rrips | | % IMPACT | ACT | |
| ROADWAY | FROM | TO | LANES | VOLUME | ASSIGNIVILINI | : IOO /NII | NB/EB | SB/WB | NB/EB | | Sig? SB/WB | Sig? |
| | | | | | | | | | | | | |
| Military Tr | Atlantic Ave | Sherwood Blvd | QT9 | 2,680 | 20% | 0 | 5 | 80 | 0.19% | No | 0.30% | No |
| Military Tr | Sherwood Blvd | Linton Blvd | QT9 | 2,680 | 20% | - | 80 | 2 | 0.30% | N _o | 0.19% | 8 |
| Military Tr | Linton Blvd | Clint Moore Rd | QT9 | 2,680 | 20% | - | 3 | 2 | 0.11% | No | 0.07% | No |
| | | | | | | | | | | | | |
| Linton Blvd | Sims Rd | Military Tr | 4LD | 1,770 | 15% | - | 2 | - | 0.11% | 8 | %90.0 | 8 |
| Linton Blvd | Military Tr | Homewood Blvd | QT9 | 2.680 | 15% | 0 | _ | 2 | 0.04% | 8 | 0.07% | 9 |



CONCLUSION

As shown in the foregoing analysis, the proposed development program meets Palm Beach County Traffic Performance Standards requirements.

If there are any questions regarding the information provided herein, please contact me at (561) 840-0852 or stephanie.guerra@kimley-horn.com.

Sincerely

ANIE A. G

Stephanto Gargo P.E.

Transportation Engineer


Florida Registration

Number 842000

Engineer 942000

Registry Nd IBd 106

Attachments







Project Site

DRIVEWAY VOLUMES DELRAY 36








Florida

Broth Be



TAC 1358 01/23/2024

Site Plan

SHEET # SP.1