

**DELRAY BEACH CITY OF
 OILMANS 2500 GAL FUEL TRUCK**

QUOTATION

M2 106 CONVENTIONAL CHASSIS

SET BACK AXLE - TRUCK	14,600# FLAT LEAF FRONT SUSPENSION
CUM L9 300 HP @ 2000 RPM, 2200 GOV RPM, 860 LB/FT @ 1300 RPM	106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	5275MM (208 INCH) WHEELBASE
RS-26-185 26,000# T-SERIES SINGLE REAR AXLE	11/32X3-1/2X10-15/16 INCH STEEL FRAME
26,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER AND RADIUS ROD	(8.73MMX277.8MM/0.344X10.94 INCH) 120KSI
DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE	2550MM (100 INCH) REAR FRAME OVERHANG
	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT

	TOTAL # OF UNITS (1)	PER UNIT	TOTAL
VEHICLE PRICE	\$	\$	\$
EXTENDED WARRANTY	\$	\$	\$
DEALER INSTALLED OPTIONS	\$	\$	\$
CUSTOMER PRICE BEFORE TAX	\$	\$	\$

TAXES AND FEES

TAXES AND FEES	\$	\$
OTHER CHARGES	\$	\$

TRADE-IN

TRADE-IN ALLOWANCE	\$	(0)	\$	(0)
---------------------------	-----------	------------	-----------	------------

BALANCE DUE	(LOCAL CURRENCY)	\$	151,515	\$	151,515
--------------------	-------------------------	-----------	----------------	-----------	----------------

COMMENTS: Projected delivery on ____ / ____ / ____ provided the order is received before ____ / ____ / ____.

APPROVAL: Please indicate your acceptance of this quotation by signing below: Customer:

X _____ Date: ____ / ____ / ____.

Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtfoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at www.daimler-truckfinancial.com.

S P E C I F I C A T I O N P R O P O S A L

Description	
Price Level	M2 PRL-16M (EFF:04/25/17)
Data Version	SPECPRO21 DATA RELEASE VER 011
Vehicle Configuration	<p>M2 106 CONVENTIONAL CHASSIS 2019 MODEL YEAR SPECIFIED SET BACK AXLE - TRUCK STRAIGHT TRUCK PROVISION LH PRIMARY STEERING LOCATION</p>
General Service	<p>TRUCK CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) PICKUP AND DELIVERY/SHORT HAUL SERVICE GOVERNMENT BUSINESS SEGMENT FIXED LOAD COMMODITY TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS MAXIMUM 8% EXPECTED GRADE MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE MEDIUM TRUCK WARRANTY EXPECTED FRONT AXLE(S) LOAD : 14600.0 lbs EXPECTED REAR DRIVE AXLE(S) LOAD : 26000.0 lbs EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 40600.0 lbs</p>
Truck Service	

Description

TANK BODY
3-V DISTRIBUTING INC
EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE
FRAME "XX" INCHES : 32.0 in

Engine

CUM L9 300 HP @ 2000 RPM, 2200 GOV RPM,
860 LB/FT @ 1300 RPM

Electronic Parameters

75 MPH ROAD SPEED LIMIT
CRUISE CONTROL SPEED LIMIT SAME AS ROAD
SPEED LIMIT
PTO MODE BRAKE OVERRIDE - SERVICE
BRAKE APPLIED
PTO RPM WITH CRUISE SET SWITCH - 700 RPM
PTO RPM WITH CRUISE RESUME SWITCH - 800
RPM
PTO MODE CANCEL VEHICLE SPEED - 5 MPH
PTO GOVERNOR RAMP RATE - 250 RPM PER
SECOND
PTO MINIMUM RPM - 700
REGEN INHIBIT SPEED THRESHOLD - 5 MPH

Engine Equipment

2016 ONBOARD DIAGNOSTICS/2010
EPA/CARB/FINAL GHG17 CONFIGURATION
NO 2008 CARB EMISSION CERTIFICATION
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
ONE PIECE VALVE COVER
SIDE OF HOOD AIR INTAKE WITH FIREWALL
MOUNTED DONALDSON AIR CLEANER
DR 12V 240 AMP 40-SI BRUSHLESS PAD
ALTERNATOR WITH REMOTE BATTERY
VOLTAGE SENSE
(3) ALLIANCE MODEL 7T31, GROUP 31, 12 VOLT
2190 CCA THREADED STUD BATTERIES
BATTERY BOX FRAME MOUNTED
STANDARD BATTERY JUMPERS
SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE UNDER CAB

Description

WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN
NON-POLISHED BATTERY BOX COVER
CUMMINS TURBOCHARGED 18.7 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE
STANDARD MECHANICAL AIR COMPRESSOR
GOVERNOR
AIR COMPRESSOR DISCHARGE LINE
ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM
CUMMINS EXHAUST BRAKE INTEGRAL WITH
VARIABLE GEOMETRY TURBO WITH ON/OFF
DASH SWITCH
RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND DASH MOUNTED REGENERATION
REQUEST SWITCH
10 FOOT 00 INCH (120 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT
RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP
23 GALLON DIESEL EXHAUST FLUID TANK
100 PERCENT DIESEL EXHAUST FLUID FILL
LH MEDIUM DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID PUMP
MOUNTING
STANDARD DIESEL EXHAUST FLUID TANK CAP
ALUMINUM AFTERTREATMENT
DEVICE/MUFFLER/TAILPIPE SHIELD(S)
HORTON DRIVEMASTER ADVANTAGE ON/OFF
FAN DRIVE
AUTOMATIC FAN CONTROL WITHOUT DASH
SWITCH, NON ENGINE MOUNTED
CUMMINS SPIN ON FUEL FILTER
COMBINATION FULL FLOW/BYPASS OIL FILTER
1100 SQUARE INCH ALUMINUM RADIATOR
ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE-
CHARGED SCA HEAVY DUTY COOLANT

Description

GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
ALUMINUM FLYWHEEL HOUSING
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 145 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODEL RDS

ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

LOAD BASED SHIFT SCHEDULE AND VEHICLE ACCELERATION CONTROL RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY VOCATIONAL USAGE

NEUTRAL AT STOP - DISABLED, FUELSENSE - DISABLED

Description

DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES
CUSTOMER INSTALLED CHELSEA 277 SERIES PTO
PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED
TRANSMISSION PROGNOSTICS - ENABLED 2013
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74
DROP SINGLE FRONT AXLE
MERITOR 16.5X5 Q+ CAST SPIDER HEAVY DUTY CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL
STANDARD SPINDLE NUTS FOR ALL AXLES
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS
TRW TAS-85 POWER STEERING
POWER STEERING PUMP
2 QUART SEE THROUGH POWER STEERING RESERVOIR
SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

14,600# FLAT LEAF FRONT SUSPENSION

Description

GRAPHITE BRONZE BUSHINGS WITH SEALS -
FRONT SUSPENSION
NO FRONT SHOCK ABSORBERS

Rear Axle and Equipment

RS-26-185 26,000# T-SERIES SINGLE REAR
AXLE
5.38 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH STANDARD
AXLE HOUSING
SPL170 XL DANA SPICER MAIN DRIVELINE WITH
HALF ROUND YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - SINGLE REAR AXLE
(1) DRIVER CONTROLLED DIFFERENTIAL LOCK
REAR VALVE FOR SINGLE DRIVE AXLE
BLINKING LAMP WITH EACH MODE SWITCH,
DIFFERENTIAL UNLOCK WITH IGNITION OFF,
ACTIVE <5 MPH
MERITOR 16.5X7 P CAM REAR BRAKES,
DOUBLE ANCHOR, CAST SHOES
NON-ASBESTOS REAR BRAKE LINING
BRAKE CAMS AND CHAMBERS ON REAR SIDE
OF DRIVE AXLE(S)
WEBB HEAVY WEIGHT CAST IRON REAR BRAKE
DRUMS
REAR BRAKE DUST SHIELDS
REAR OIL SEALS
BENDIX EVERSURE LONGSTROKE HEAVY DUTY
30/36 1-DRIVE AXLE SPRING PARKING
CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
ROADRANGER SYNTHETIC FE 75W-90 REAR
AXLE LUBE

Rear Suspension

26,000# FLAT LEAF SPRING REAR SUSPENSION
WITH HELPER AND RADIUS ROD
SPRING SUSPENSION - NO AXLE SPACERS
STANDARD AXLE SEATS IN AXLE CLAMP
GROUP
FORE/AFT CONTROL RODS

Brake System

Description

AIR BRAKE PACKAGE
WABCO 4S/4M ABS WITHOUT TRACTION
CONTROL
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
FIBER BRAID PARKING BRAKE HOSE
STANDARD BRAKE SYSTEM VALVES
STANDARD AIR SYSTEM PRESSURE
PROTECTION SYSTEM
STD U.S. FRONT BRAKE VALVE
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
BW AD-IS (DRM) BRAKE LINE AIR DRYER WITH
SHIELD, HEATER AND INTEGRAL RESERVOIR
AIR DRYER RESERVOIR MOUNTED
STEEL AIR BRAKE RESERVOIRS
PETCOCK DRAIN VALVES ON ALL AIR TANK(S)

Trailer Connections

UPGRADED CHASSIS MULTIPLEXING UNIT
UPGRADED BULKHEAD MULTIPLEXING UNIT

Wheelbase & Frame

5275MM (208 INCH) WHEELBASE
11/32X3-1/2X10-15/16 INCH STEEL FRAME
(8.73MMX277.8MM/0.344X10.94 INCH) 120KSI
1/4 INCH (6.35MM) C-CHANNEL INNER FRAME
REINFORCEMENT
2550MM (100 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 91 INCH TO 100
INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
142.45 in
CALCULATED EFFECTIVE BACK OF CAB TO
REAR SUSPENSION C/L (CA) : 139.45 in
CALC'D FRAME LENGTH - OVERALL : 337.39
CALC'D SPACE AVAILABLE FOR DECKPLATE :
142.45 in
CALCULATED FRAME SPACE LH SIDE : 113.33
in
CALCULATED FRAME SPACE RH SIDE : 90.9 in
SQUARE END OF FRAME

Description

FRONT CLOSING CROSSMEMBER
LIGHTWEIGHT HEAVY DUTY ALUMINUM ENGINE
CROSSMEMBER
STANDARD MIDSHIP #1 CROSSMEMBER(S)
STANDARD REARMOST CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER

Chassis Equipment

THREE-PIECE 14 INCH STEEL CENTER BUMPER
WITH FLEXIBLE PLASTIC ENDS
FRONT TOW HOOKS - FRAME MOUNTED
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
FENDER AND FRONT OF HOOD MOUNTED
FRONT MUDFLAPS
GRADE 8 THREADED HEX HEADED FRAME
FASTENERS

Fuel Tanks

50 GALLON/189 LITER RECTANGULAR
ALUMINUM FUEL TANK - RH
50 GALLON/189 LITER RECTANGULAR
ALUMINUM FUEL TANK - LH
RECTANGULAR FUEL TANK(S)
PLAIN ALUMINUM/PAINTED STEEL
FUEL/HYDRAULIC TANK(S) WITH PAINTED
BANDS
FUEL TANK(S) AFT
PLAIN STEP FINISH
FUEL TANK CAP(S)
DETROIT FUEL/WATER SEPARATOR WITH
WATER IN FUEL SENSOR
EQUIFLO INBOARD FUEL SYSTEM
NO NATURAL GAS VEHICLE FUEL TANK VENT
LINE/STACK
HIGH TEMPERATURE REINFORCED NYLON
FUEL LINE

Tires

CONTINENTAL HSC1 12R22.5 16 PLY RADIAL
FRONT TIRES
CONTINENTAL HSC1 12R22.5 16 PLY RADIAL
REAR TIRES

Description

Hubs

CONMET PRESET PLUS PREMIUM IRON FRONT
HUBS
CONMET PRESET PLUS PREMIUM IRON REAR
HUBS

Wheels

MAXION WHEELS 10041 22.5X9.00 10-HUB PILOT
5.25 INSET 5-HAND STEEL DISC FRONT
WHEELS
MAXION WHEELS 10047 22.5X9.00 10-HUB PILOT
5-HAND STEEL DISC REAR WHEELS
FRONT WHEEL MOUNTING NUTS
REAR WHEEL MOUNTING NUTS

Cab Exterior

106 INCH BBC FLAT ROOF ALUMINUM
CONVENTIONAL CAB
LEAF SPRING REAR CAB SUSPENSION
LH AND RH GRAB HANDLES
PAINTED PLASTIC GRILLE
ARGENT SILVER HOOD MOUNTED AIR INTAKE
GRILLE
FIBERGLASS HOOD
SINGLE ELECTRIC HORN
DOOR LOCKS AND IGNITION SWITCH KEYED
THE SAME
REAR LICENSE PLATE MOUNT END OF FRAME
INTEGRAL HEADLIGHT/MARKER ASSEMBLY
(5) AMBER MARKER LIGHTS
INTEGRAL STOP/TAIL/BACKUP LIGHTS
STANDARD FRONT TURN SIGNAL LAMPS
DUAL WEST COAST MOLDED-IN COLOR
MIRRORS
DOOR MOUNTED MIRRORS
102 INCH EQUIPMENT WIDTH
LH AND RH 8 INCH MOLDED-IN COLOR CONVEX
MIRRORS MOUNTED UNDER PRIMARY
MIRRORS
STANDARD SIDE/REAR REFLECTORS
63X14 INCH TINTED REAR WINDOW

Description

TINTED DOOR GLASS LH AND RH WITH TINTED
NON-OPERATING WING WINDOWS
MANUAL DOOR WINDOW REGULATORS
TINTED WINDSHIELD
2 GALLON WINDSHIELD WASHER RESERVOIR
WITHOUT FLUID LEVEL INDICATOR, FRAME
MOUNTED

Cab Interior

OPAL GRAY VINYL INTERIOR
MOLDED PLASTIC DOOR PANEL
MOLDED PLASTIC DOOR PANEL
BLACK MATS WITH SINGLE INSULATION
FORWARD ROOF MOUNTED CONSOLE WITH
UPPER STORAGE COMPARTMENTS WITHOUT
NETTING
IN DASH STORAGE BIN
(2) CUP HOLDERS LH AND RH DASH
GRAY/CHARCOAL FLAT DASH
HEATER, DEFROSTER AND AIR CONDITIONER
STANDARD HVAC DUCTING
MAIN HVAC CONTROLS WITH RECIRCULATION
SWITCH
STANDARD HEATER PLUMBING
DENSO HEAVY DUTY AIR CONDITIONER
COMPRESSOR
BINARY CONTROL, R-134A
STANDARD INSULATION
SOLID-STATE CIRCUIT PROTECTION AND
FUSES
12V NEGATIVE GROUND ELECTRICAL SYSTEM
DOME LIGHT WITH 3-WAY SWITCH ACTIVATED
BY LH AND RH DOORS
CAB DOOR LATCHES WITH MANUAL DOOR
LOCKS
BASIC HIGH BACK AIR SUSPENSION DRIVER
SEAT WITH MECHANICAL LUMBAR AND
INTEGRATED CUSHION EXTENSION
2 MAN TOOL BOX MID BACK NON SUSPENSION
PASSENGER SEAT
LH AND RH INTEGRAL DOOR PANEL ARMRESTS
VINYL WITH VINYL INSERT DRIVER SEAT

Description

VINYL WITH VINYL INSERT PASSENGER SEAT
BLACK SEAT BELTS
FIXED STEERING COLUMN
4-SPOKE 18 INCH (450MM) STEERING WHEEL
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

GRAY DRIVER INSTRUMENT PANEL
GRAY CENTER INSTRUMENT PANEL
BLACK GAUGE BEZELS
LOW AIR PRESSURE INDICATOR LIGHT AND
AUDIBLE ALARM
2 INCH PRIMARY AND SECONDARY AIR
PRESSURE GAUGES
INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS
ELECTRONIC CRUISE CONTROL WITH
SWITCHES IN LH SWITCH PANEL
KEY OPERATED IGNITION SWITCH AND
INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28
LED WARNING LAMPS AND DATA LINKED
HEAVY DUTY ONBOARD DIAGNOSTICS
INTERFACE CONNECTOR LOCATED BELOW LH
DASH
2 INCH ELECTRIC FUEL GAUGE
PROGRAMMABLE RPM CONTROL -
ELECTRONIC ENGINE
ELECTRICAL ENGINE COOLANT TEMPERATURE
GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE
GAUGE
ENGINE AND TRIP HOUR METERS INTEGRAL
WITHIN DRIVER DISPLAY
CUSTOMER FURNISHED AND INSTALLED PTO
CONTROLS
ELECTRIC ENGINE OIL PRESSURE GAUGE
AM/FM/WB WORLD TUNER RADIO WITH
BLUETOOTH AND USB AND AUXILIARY INPUTS,
J1939
DASH MOUNTED RADIO

Description

(2) RADIO SPEAKERS IN CAB
AM/FM ANTENNA MOUNTED ON FORWARD LH
ROOF
ELECTRONIC MPH SPEEDOMETER WITH
SECONDARY KPH SCALE, WITHOUT
ODOMETER
STANDARD VEHICLE SPEED SENSOR
ELECTRONIC 3000 RPM TACHOMETER
NO VEHICLE PERFORMANCE MONITOR
IDLE LIMITER, ELECTRONIC ENGINE
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR
WITH DELAY
MARKER LIGHT SWITCH INTEGRAL WITH
HEADLIGHT SWITCH
ONE VALVE PARKING BRAKE SYSTEM WITH
WARNING INDICATOR
SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, WASHER/WIPER AND HAZARD IN
HANDLE
INTEGRAL ELECTRONIC TURN SIGNAL
FLASHER WITH HAZARD LAMPS OVERRIDING
STOP LAMPS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EB WHITE ELITE BC
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
PAINT
POWDER WHITE (N0006EA) FRONT
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
POWDER WHITE (N0006EA) REAR
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
BUMPER PAINT: FP24812 ARGENT SILVER
DUPONT FLEX
STANDARD E COAT/UNDERCOATING

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

**2018 FLORIDA SHERIFFS CONTRACT
SPEC 13
LOU BACHRODT/SBL FREIGHTLINER
LOW BID ON THIS SPEC**

Prepared by:
Drew Ellison
LOU BACHRODT FREIGHTLINER
2840 CENTER PORT CIRCLE
POMPANO BEACH, FL 33064
Phone: 407-886-6704

Dealer Installed Options

	Weight Front	Weight Rear
2500 GALLON FUEL TRUCK PER ATTACHED SPECS	0	0
Total Dealer Installed Options	0 lbs	0 lbs