BUILDING MATERIALS AND COLOR SAMPLE FORM

NOTE THE TYPE OF MATERIAL AND COLOR SPECIFICATION PROPOSED INCLUDING TYPES OF FINISHES. CAN ATTACH IMAGES OR PHOTOS OF MATERIALS.

ATTACH ACTUAL PAINT COLOR SAMPLES WITH DETAILS OF MANUFACTURER

| ROOF | WALLS |
|--|--|
| ROOF ROOF DECK AND PARKING LEVEL BASIS OF DESIGN (VEHIHICLE): HENRY DUNDEQ DECK COATINGS; TRAFFIC SYSTEM - FULLY SEED AND LOCK SYSTEM BASIS OF DESIGN (PEDESTRIAN, LIGHT TRAFFIC): HENRY PUMADEQ SYSTEM - PEDESTRIAN TRAFFIC COATING | 8 INCH AND 12 INCH CMU WALL, FINISHED WITH 3-COAT STUCCO SYSTEM ON FLUID APPLIED VAPOR BARRIER. STUCCO FINISH TO BE "FINE SAND SMOOTH" PAINTED SHERWIN WILLIAMS, SW7005 PURE WHITE |
| FASCIA | TRIM/OTHER |
| ALUMINUM COMPOSITE PANEL BASIS OF DESIGN: REYNOBOND ACM COLONIAL READ; FAUX WOOD FINISH WITH GRAIN MOUNT TO PANEL CHANNEL SUBFRAMING PER MFR GUIDELINES | PERFORATED PANELS AT GARAGE OPENINGS BASIS OF DESIGN; McNICHOLS CO. AL/3003H14 0.062GA 3/8Ø ROUND PERFORATED @ 1/2" STAGGERED OPTION I: PAINTED TO MATCH STOREFRONT "DOVE GRAY" OPTION 2: PAINTIED SHERWIN WILLIAMS SW6920 CENTER STAGE (GREEEN) |
| WINDOWS | SHUTTERS/AWNINGS |
| LOW TO NO LEAD GLASS BASIS OF DESIGN: VIRACON I" LAMINATED INSULATED VE24-85 VLT: 80%; SOLAR ENERGY 55%; UV: <1%; U-VALUE - WINTER: 0.46 BTU, SUMMER; 0.47 BTU SHADING COEF: 0.67; SOLAR HEAD GAIN COEF: 0.58 STOREFRONT WINDOWS: BASIS OF DESIGN KAWNEER 45 IT, POWDERED-COATED DOVE GRAY | NOT APPLICABLE |
| RAILINGS | FENCE |
| GLASS RAILINGS WITH ALUMINUM POSTS BASIS OF DESIGN CRL ARCHITECTURAL GLASS RAILINGS GRS ROUND RAILING CAPS CRL POST RAILING POSTS SYSTEM METAL POWDER COATED TO MATCH STOREFRONT "DOVE GRAY" | NOT APPLICABLE |
| COLUMNS | OTHER |
| I. STUCCO FINISH, SEE ABOVE UNDER WALLS. 2. WRAPPED IN ALUMINUM COMPOSIT PANEL, SEE ABOVE UNDER FASCIA. | ACCENT TILES: BASIS OF DESIGN MARKET COLLECTION VIHARA-VINYASA; IXI BLUE MOSIAC VIHARA-AKASHA IXI GRAY TILE TREND GROUP BRILLIANTE "251": 3/4 x 3/4 GREEN/SEAFOAM GREEN |