

[illegible]

Figure 1: Window and door details. The figure shows six elevation drawings of window and door units, labeled A through F, with their dimensions and mounting types. A horizontal line at the bottom of each drawing indicates the 'TOP OF SLAB'.

- Unit A (FIXED):** A double window unit. Total width is 6'-0" (EQ. on each side). Total height is 9'-0" (7'-6" for the window, 1'-6" for the sill). Mounting is FIXED.
- Unit B (FIXED):** A single window unit. Total width is 2'-5". Total height is 9'-0" (6'-0" for the window, 3'-0" for the sill). Mounting is FIXED.
- Unit C (FIXED):** A single window unit. Total width is 2'-6". Total height is 8'-0" (5'-0" for the window, 3'-0" for the sill). Mounting is FIXED.
- Unit D (CASEMENT):** A double window unit. Total width is 5'-0" (2'-6" on each side). Total height is 8'-0" (5'-0" for the window, 3'-0" for the sill). Mounting is CASEMENT.
- Unit E (CASEMENT):** A single window unit. Total width is 2'-6". Total height is 8'-0" (5'-0" for the window, 3'-0" for the sill). Mounting is CASEMENT.
- Unit F (FIXED):** A single window unit. Total width is 2'-6". Total height is 8'-0" (5'-6" for the window, 2'-6" for the sill). Mounting is FIXED.
- Unit G (FIXED):** A triple window unit. Total width is 7'-6" (2'-6" on each side, 2'-6" in the middle). Total height is 8'-0" (6'-0" for the window, 2'-0" for the sill). Mounting is FIXED.

[illegible]

1. ALL EXTERIOR GLAZING UNITS SHALL BE IMPACT RESISTANT WITH FLORIDA PRODUCT APPROVAL.
(SHADING COEFFICIENT OF GLAZING SHALL COMPLY WITH FLORIDA ENERGY CALCULATIONS).
2. COORDINATE ALL ROUGH OPENINGS WITH WINDOW / DOOR MANUFACTURER - ALL DIMENSIONS ARE NOMINAL (CONCRETE OR ROUGH OPENING) DIMENSIONS, PROVIDE ENGINEERED SHOP DRAWINGS & METRO DADE PRODUCT APPROVAL NOTICES FOR ALL WINDOWS, EXT. DOORS.
3. ALL WINDOWS / DOORS SHALL COMPLY WITH F.B.C. 6TH EDITION (2017).
4. PROVIDE SHOP DRAWINGS FOR ALL GLAZING FOR ARCHITECTS REVIEW AND APPROVAL PRIOR TO FABRICATION.
5. ALL DOORS TO COMPLY WITH CODE. IMPACT AND WIND LOAD REQUIREMENTS (SUBMIT MANUFACTURES CUT SHEET / PRODUCT APPROVALS).
6. FIELD VERIFY ALL WINDOW AND DOOR OPENINGS PRIOR TO FABRICATION.
7. ALL WINDOWS NOTED AS EGRESS WINDOWS SHALL COMPLY WITH F.B.C. SILL HEIGHT SHALL NOT EXCEED 44" A.F.F. MIN. OPG. HT. SHALL BE 24" MIN OPG. WIDTH SHALL BE 20" MIN. CLEAR OPENING AREA SHALL BE 7 SQ. FT. (5.0 SQ. FT. @ 1ST FLOOR).
8. ALL EGRESS WINDOWS IN SLEEPING ROOM SHOULD HAVE A MINIMUM CLEAR OPENING OF 5.7 SQ. FT.
9. ALL EXTERIOR DOORS / WINDOWS SHALL BE INSTALLED PER FLORIDA PRODUCT APPROVAL..
10. ALL MUNTINS TO BE 1.0" WIDE RAISED TYPE ON BOTH INSIDE AND OUTSIDE OF WINDOW.
11. APPLY SHERWIN WILLIAMS SHER-CRETE FLEXIBLE CONCRETE WATER PROOF (TEXTURED A5 SERIES) AT EXTERIOR PERIMETER OF ALL DOOR & WINDOW MASONRY OPENINGS TO A DISTANCE OF 12" FROM EDGE OF OPENING UNLESS OTHERWISE NOTED.
12. USE LOUVERED DOOR AT HT. HC. C. OSET IF NO RETURN AIR IS PROVIDED.
13. ALL WINDOW FRAMES TO BE WHITE ALUMINUM.
14. REFER TO ELEVATIONS AND SECTIONS FOR OPERABLE WINDOW SWING ORIENTATION.
15. ALL GLAZING TO BE CLEAR NON-REFLECTANT.

Figure 1 displays eight elevation views of window and door types, labeled 1 through 8, showing their dimensions and panel configurations. The views are arranged in three rows, with a horizontal line labeled "TOP OF SLAB" at the bottom of each row.

- View 1:** A single door with a height of 10'-0" and a width of 3'-4" (overall) and 3'-0" (opening). It features a "SOLID RECESSED PANEL".
- View 2:** A row of five windows with a total height of 10'-0" and a total width of 15'-0". Each window has a height of 4'-0" and a width of 3'-0". They feature a "SOLID RECESSED PANEL TYP".
- View 3:** A row of three windows with a total height of 10'-0" and a total width of 10'-6". Each window has a height of 4'-0" and a width of 3'-6".
- View 4:** A single door with a height of 9'-0" and a width of 2'-10" (overall) and 2'-6" (opening). It features a "SOLID RECESSED PANEL".
- View 5:** A row of five windows with a total height of 8'-0" and a total width of 16'-4". Each window has a height of 3'-6" and a width of 3'-0". They feature a "SOLID RECESSED PANEL TYP".
- View 6:** A row of four windows with a total height of 8'-0" and a total width of 12'-0". Each window has a height of 4'-0" and a width of 3'-0".
- View 7:** A single door with a height of 8'-0" and a width of 2'-10" (overall) and 2'-6" (opening). It features a "SOLID RECESSED PANEL".
- View 8:** A row of three windows with a total height of 8'-0" and a total width of 10'-0". Each window has a height of 4'-0" and a width of 3'-0".

A-5

RICHARD JONES ARCHITECTURE