

PROJECT TEAM

100 EAST PINE STREET, SUITE 404

CONTACT: JO STAFFELBACH HEINZ

KIMLEY-HORN AND ASSOCIATES, INC.

CONTACT: JÁSON A. WEBBER, P.E.

KIMLEY-HORN AND ASSOCIATES, INC.

LANDSCAPE ARCHITECT

1920 WEKIVA WAY, SUITE 200 WEST PALM BEACH, FL 33411

CONTACT: TRICIA RICHTER, PLA

PERIMETER SURVEYING & MAPPING

CONTACT: JEFF S. HODAPP, PLS

1615 SOUTH CONGRESS AVENUE, SUITE 201

ARCHITECT: ROBERT CARLSON

ARCHITECT/CLIENT

PHONE: (214) 452-1283

PHONE: (913) 897-7811

DELRAY BEACH, FL 33445

PHONE: (561) 404-7250

PHONE: (561) 840-0846

947 CLINT MOORE ROAD

BOCA RATON, FL 33487

PHONE: (561) 241-9988

SURVEYOR


ORLANDO, FL 32801

CIVIL ENGINEER

DLR GROUP

CLASS III SITE PLAN COLLIER CAR CLUB FOR DLR GROUP, INC. DELRAY BEACH, FL

FEBRUARY 2019



PROJECT LOCATION 777 S. CONGRESS AVE.

DELRAY BEACH, FL 33445

THE PRESENCE OF GROUNDWATER SHOULD BE

INCLUDE CONSIDERATION FOR ADDRESSING THIS ISSUE AND OBTAINING ALL NECESSARY PERMITS

ANTICIPATED. CONTRACTOR'S BID SHALL

Sheet	Sheet Title
Number	
C0.00	COVER SHEET
C0.01	GENERAL NOTES
C0.02	GENERAL NOTES
C2.00	DEMOLITION PLAN
C4.00	SITE PLAN
C4.10	SITE DETAILS
C4.11	SITE DETAILS
C5.00	ENGINEERING PLAN
C5.10	ENGINEERING DETAILS
C5.11	ENGINEERING DETAILS
C6.00	COMPOSITE PLAN
C7.00	VEHICLE MOVEMENT PLAN — PASSENGER CAR
C7.01	VEHICLE MOVEMENT PLAN — LARGE TRUCK
C7.02	VEHICLE MOVEMENT PLAN — FIRE TRUCK
L0.00	TREE DISPOSITION PLAN
L0.01	TREE DISPOSITION PLAN
L1.00	LANDSCAPE PLAN
L1.01	LANDSCAPE PLAN
L1.10	LANDSCAPE DETAILS
L1.11	LANDSCAPE NOTES

SHEET INDEX (E	BY OTHERS)
Sheet Number	Sheet Title
1 OF 1	SURVEY
A1.0	FLOOR PLAN
A2.0	BUILDING ELEVATIONS
A3.0	CONGRESS STREET RENDERINGS
A3.1	I-95 RENDERINGS
E-1	PHOTOMETRIC PLAN
E-2	PHOTOMETRIC RENDERING

	SHEET INDEX (BY OTHERS)					
	Sheet Number	Sheet Title				
	1 OF 1	SURVEY				
	A1.0	FLOOR PLAN				
	A2.0	BUILDING ELEVATIONS				
	A3.0	CONGRESS STREET RENDERINGS				
	A3.1	I-95 RENDERINGS				
	E-1	PHOTOMETRIC PLAN				
	E-2	PHOTOMETRIC RENDERING				
,						


PLANS ARE IN NAVD 1988 DATUM CONVERSION EQUATION IS BELOW: (NAVD 1988) + 1.53' = (NGVD 1929)


Always call 811 two full business days before you dig to have underground utilities located and marked. Sunshine 811.com


SHEET NUMBER C0.00

SHEE-

COVER







PROPERTY LINE — — CENTERLINE OF R/W PARKING STALL COUNT ADA PARKING STALL

--- x ----- SECURITY FENCE PROPOSED CONCRETE SIDEWALK

PROPOSED LIGHT POLES (SEE PHOTOMETRIC PLANS FOR DETAILS)

HORIZONTAL CONTROL NOTES

- 1. ALL CURBING IS TYPE "D" UNLESS OTHERWISE STATED.
- 2. TYPE "D" CURB SHALL BE CONSTRUCTED PER FDOT INDEX. ALL TYPE "D" CURB SHALL HAVE A 3' STRAIGHT TRANSITION AT THE BEGINNING AND ENDING POINTS WHEN NOT CONNECTING TO TYPE "F" CURB AND GUTTER.
- 3. ALL DIMENSIONS SHOWN ARE TO FACE OF CURB FOR TYPE "D" CURB OR EDGE OF PAVEMENT FOR NO CURB, UNLESS OTHERWISE NOTED.
- 4. ALL CURB RAMPS AND SIDEWALKS ENTERING PARKING OR TRAVEL WAYS SHALL HAVE DETECTABLE WARNING SURFACES 2' DEEP AND THE WIDTH OF THE SIDEWALK. REFER TO THE LATEST FDOT DESIGN STANDARDS
- 5. ALL STOP BARS AND CROSSWALKS SHALL BE PAINT.
- 6. REFER TO LANDSCAPE PLANS FOR PLANTING AND DETAILS.
- 7. ALL PROPOSED IMPROVEMENTS SHALL BE IN COMPLIANCE WITH THE FLORIDA FIRE PREVENTION CODE 6TH EDITION - FLORIDA SPECIFIC NFPA 1 FIRE CODE, 2015 EDITION AND FLORIDA SPECIFIC NFPA 101 LIFE SAFETY CODE, 2015 EDITION.

142

8. SECURITY FENCE SHALL BE METAL FENCE WITH MAX 26" SQUARE COLUMNS, SPACED 8'-10' O.C.

		PARCEL INFURIMATION			
	PROJECT NAME	COLLIER CAR CLUB			
	ADDRESS	777 S. CONGRESS AVE., D	ELRAY BEACH, FL 33445		
	PBC PROPERTY APPRAISER FOLIO #	12-43-46-19-0	0-000-1060		
	ZONING DESIGNATION	MIXED RESIDENTIAL, OFFICE	, AND COMMERICAL (MROC)		
FUTURE LAND USE CMU (CONGRESS AVE MIXED USE)					
	PROPOSED ZONING	SPECIAL ACTIVITIES DISTRICT (SAD)			
	FEMA FLOOD ZONE	COMMUNITY PANEL 12099C0979F (ZONE X) (NO BFE)			
		PROJECT AREAS			
		EVICTING	DDODOGED		

	COMMONITY PANEL 12099C09/9F (ZONE X) (NO BFE)						
	PROJEC	PROJECT AREAS					
·	E	(ISTING:	PROP	OSED:			
TOTAL AREA	209,978	100.0%	209,978	100.0%			
IMPERVIOUS TOTAL	119,917	57.1%	119,192	56.8%			
PAVEMENT	66,674	31.8%	65,950	31.4%			
BUILDING FOOTPRINT	53,243	25.4%	53,243	25.4%			
PERVIOUS TOTAL	90,062	42.9%	90,786	43.2%			
OPEN SPACE (25% MIN.)	90,062	42.9%	82,161	39.1%			
GRASS PARKING	N/A	N/A	8,625	4.1%			
LOT COVERAGE (75% MAX.)	119,917	57.1%	119,192	56.8%			

	PARKING		
	BUILDING:	RATIO:	REQUIRED:
OFFICE (FIRST 3,000 SF)	3,000	4 SPACES PER 1,000SF	12
OFFICE (POST 3,000 SF)	3,350	3.5 SPACES PER 1,000SF	12
VEHICLE STORAGE	240 CARS	0.25 SPACES PER BAY	60
TOTAL REQUIRED			84
	KING PROVIE	DED	
EMPLOYEE/CUSTOMER/SERVICE PARKING		102	
COMPACT/GRASS PARKING	35		

	LOADING ZONE	
	CODE REQUIREMENT:	PROVIDED:
BUILDING USE: OFFICE	20,000 TO 100,000 SF = TWO BERTHS	TWO BERTHS
LOADING SPACE WIDTH	12'	12'
LOADING SPACE LENGTH	30'	30'
VERTICAL CLEARANCE	12'	N/A

DEVELOPMENT STANDARDS (SEC. 4.3.4)					
	CODE REQUIREMENT:	PROVIDED:			
FRONTAGE	0' MINIMUM	565'			
WIDTH	0' MINIMUM	559'			
DEPTH	0' MINIMUM	365'			
SITE AREA	0 ACRE MINIMUM	4.82 ACRES			
HEIGHT	48' MAXIMUM	26' 6''			
BUILDING AREA	N/A	53,243 SF			
	BUILDING SETBAC				
	REQUIRED:	PROVIDED:			
FRONT (WEST)	15'	95.5'			
SIDE (NORTH)	15'	127.6'			
SIDE (SOUTH)	15'	175.4'			
REAR (EAST)	25'	19.5' (exist. non-conformity)			

THE PRESENCE OF GROUNDWATER SHOULD BE

INCLUDE CONSIDERATION FOR ADDRESSING THIS

ISSUE AND OBTAINING ALL NECESSARY PERMITS.

ANTICIPATED. CONTRACTOR'S BID SHALL

PLANS ARE IN NAVD 1988 DATUM CONVERSION EQUATION IS BELOW: (NAVD 1988) + 1.53' = (NGVD 1929)

Always call 811 two full business days before you dig to have underground utilities located and marked.

Sunshine 811.com


COLLIER CAF	CLUB PREPARED FOR
-------------	----------------------


SHEET NUMBER C4.00

Kim

S

10





PAVING, GRADING AND DRAINAGE NOTES

- THE CROSS SLOPE ON ADA ACCESSIBLE ROUTES SHALL NOT EXCEED 2.0%. THE LONGITUDINAL SLOPE ON ADA ACCESSIBLE ROUTES (NOT INCLUDING RAMPS) SHALL NOT EXCEED 5.0%. THE LONGITUDINAL SLOPE FOR RAMPS SHALL NOT EXCEED 1V:12H (8.3%). ACCESSIBLE PARKING SPACES SHALL NOT EXCEED 2.0% IN ANY DIRECTION (INCLUDING DIAGONAL).
- 2. ALL RAMPS SHALL COMPLY WITH FDOT INDEX 522-002.
- CONTRACTOR SHALL CLEAN ALL PROPOSED DRAINAGE STRUCTURES AND PIPES UPON COMPLETION OF CONSTRUCTION.
- 4. PROPOSED ELEVATIONS OF CURB REPRESENT FACE OF CURB OR EDGE OF PAVEMENT ELEVATIONS UNLESS OTHERWISE NOTED.
- PROPOSED ELEVATIONS IN ALL PERVIOUS AREAS REPRESENT FINISHED TOP OF SOD/GRASS OR ANY OTHER LANDSCAPING MATERIAL.
- 6. MATCH EXISTING GRADES AT TIE-IN LOCATIONS AT PROPERTY LINES.
- 7. TOP OF LANDSCAPED OR SODDED AREA AGAINST BUILDING SHALL BE MIN. 4" BELOW FINISH

UTILITY NOTES

- 1. CONTRACTOR SHALL FURNISH AND INSTALL NECESSARY PIPE AND FITTINGS TO TRANSITION PIPE MATERIALS WHEN REQUIRED AND TO CONNECT TO BUILDING PLUMBING.
- 2. CONTRACTOR SHALL SUPPORT AND PROTECT ALL EXISTING UTILITIES WHEN CONSTRUCTING NEW UTILITIES.
- 3. ALL MANHOLES, VALVES, CLEANOUTS AND OTHER SUCH BOXES IN PAVEMENT OR SIDEWALKS SHALL BE SET
- 4. ANY TREES OR SHRUBS PLACED WITHIN WATER, SEWER, OR DRAINAGE EASEMENTS SHALL CONFORM TO THE CITY OF DELRAY BEACH STANDARD DETAILS.
- 5. NO PROPOSED IMPROVEMENTS, BUILDINGS OR ANY KIND OF CONSTRUCTION CAN BE PLACED ON OR WITHIN ANY WATER, SEWER, OR DRAINAGE EASEMENTS, UNLESS APPROVED BY THE CITY OF DELRAY BEACH CITY
- 6. NO PROPOSED STRUCTURES SHALL BE INSTALLED WITHIN A HORIZONTAL DISTANCE OF 10-FEET FROM ANY
- EXISTING OR PROPOSED WATER, SEWER, OR DRAINAGE FACILITIES, UNLESS APPROVED BY THE CITY OF DELRAY BEACH CITY ENGINEER.
- 7. ALL WATER MAIN (WM) SHALL BE PVC C-900 DR-18 UNLESS OTHERWISE NOTED.
- 8. ALL FIRE MAIN (FM) SHALL BE DIP WITH ALL JOINTS RESTRAINED WITH MEGALUGS UNLESS OTHERWISE NOTED. ALL FIRE MAIN SHALL BE LAID AT 36" MIN. COVER. ALL FIRE RELATED CONSTRUCTION SHALL FOLLOW THE FLORIDA FIRE PREVENTION CODE 5TH EDITION - FLORIDA SPECIFIC NFPA 1, FIRE CODE, 2012 EDITION AND FLORIDA SPECIFIC NFPA 101, LIFE SAFETY CODE, 2012 EDITION.
- 9. ALL DUCTILE IRON PIPE (DIP) SHALL BE CLASS 350 UNLESS OTHERWISE NOTED. ALL DIP SHALL BE MARKED PER FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION (FDEP) STANDARDS.
- 10. ALL NEW FIRE HYDRANTS SHALL HAVE "OUT OF SERVICE" SIGNS AFFIXED AT TIME OF INSTALLATION. SIGNS SHALL REMAIN IN PLACE UNTIL THE WATER SYSTEM IS CLEARED FOR USE.
- 11. ALL WATER MAIN SHALL HAVE A MINIMUM 36" COVER OVER THE TOP OF THE PIPE UNLESS OTHERWISE NOTED. WATER AND FIRE MAINS SHALL HAVE MIN. 6" VERTICAL SEPARATION FROM EACH OTHER.
- 12. A MINIMUM HORIZONTAL DISTANCE OF 10 FEET MUST BE PROVIDED BETWEEN WATER MAINS AND STORM OR SANITARY SEWERS.ALL FITTINGS FOR WATER MAIN AND FIRE MAIN SHALL BE DUCTILE IRON MECHANICAL JOINT FITTINGS UNLESS OTHERWISE NOTED.
- 13. PIPE DEFLECTION OF WATER MAIN AND FIRE MAIN SHALL NOT EXCEED MANUFACTURER'S RECOMMENDATIONS.
- 14. PROPOSED WATER IMPROVEMENTS IN PRIVATE PROPERTY SHALL MEET PALM BEACH COUNTY HEALTH DEPARTMENT SEPARATION REQUIREMENTS, THESE CONFLICTS WILL BE ADDRESS DURING CONSTRUCTION AND WON'T AFFECT THE PUBLIC SAFETY.
- 15. CONTRACTOR SHALL COORDINATE UNDERGROUND ELECTRIC SERVICE CONNECTION WITH FPL FOR CONDUIT SIZE AND BURIED DEPTH REQUIREMENT.
- 16. THE CITY OF DELRAY BEACH UTILITIES DIVISION MUST BE GIVEN AT LEAST 48 HOURS NOTIFICATION PRIOR TO ANY SHUT-DOWN AND/OR REMOVAL OF EXISTING WATER MAIN OR SANITARY SEWER LINES.
- 17. CITY MAINTAINED UTILITIES WILL NEED TO BE TESTED AND PROTECTED (IE. PAVED AT LEAST UP TO FIRST LIFT, IF NOT ROADWAY) PRIOR TO ISSUANCE OF CERTIFICATION OF OCCUPANCY.
- 18. LEAD FREE BRASS WATER WORKS PRODUCTS SHALL MEET THE REQUIREMENT OF ASNI/AWWA C800 AND THE MAXIMUM LEAD CONTENT OF S.3872 AND NSF 61 ANNEX G. THE MANUFACTURER'S DESIGNATION AS A LEAD FREE PRODUCT SHALL BE PERMANENTLY STAMPED OR CAST INTO THE PRODUCT'S BODY. EFFECTIVE JANUARY 1, 2013, ONLY LEAD FREE BRASS WATER WORKS PRODUCTS SHALL BE INSTALLED IN CONTACT WITH POTABLE WATER.
- 19. ALL PROPOSED BACKFLOW PREVENTERS AND DOUBLE DETECTOR CHECK VALVES SHALL BE USC CERTIFIED AND LEAD FREE.
- 20. ANY TREES OR SHRUBS PLACED WITHIN WATER, SEWER OR DRAINAGE EASEMENTS SHALL CONFORM TO THE CITY OF DELRAY BEACH STANDARD DETAILS; LD 1.1 & LD 1.2.
- >21. ALL PROPOSED IMPROVEMENTS SHALL BE IN COMPLIANCE WITH THE FLORIDA FIRE PREVENTION CODE 6TH EDITION - FLORIDA SPECIFIC NFPA 1 FIRE CODE, 2015 EDITION AND FLORIDA SPECIFIC NFPA 101 LIFE SAFETY CODE, 2015 EDITION.

THE PRESENCE OF GROUNDWATER SHOULD BE

INCLUDE CONSIDERATION FOR ADDRESSING THIS

ISSUE AND OBTAINING ALL NECESSARY PERMITS.

ANTICIPATED. CONTRACTOR'S BID SHALL

<u>LEGEND</u>

PROPERTY LINE

--- F --- PROPOSED FIRE LINE PIPE PROPOSED FIRE HYDRANT --- SS --- SS --- EXISTING SANITARY PIPE EXISTING SANITARY MANHOLE --- F --- EXISTING FIRE LINE PIPE ---- w ---- EXISTING WATER PIPE EXISTING FIRE HYDRANT — FO — FO — EXISTING FIBER OPTIC LINE

---- OHL ---- EXISTING OVERHEAD LINE STORM AREA INLET STORM CURB INLET

STORM MANHOLE MATCH EXISTING ELEVATION EXISTING ELEVATION \sim FLOW ARROW

PROPOSED CONCRETE SIDEWALK PROPOSED HEAVY DUTY CONCRETE PROPOSED ASPHALT PAVEMENT

EXISTING FIRE DEPARTMENT CONNECTION

 EXISTING UTILITY EASEMENTS STORM PIPE (SEE PAVING, GRADING AND DRAINAGE PLANS) PROPOSED SPOT ELEVATION

WEBBER,

P. H.

N N Ш Ш 물 굽 **U**


Ш


PLANS ARE IN NAVD 1988 DATUM CONVERSION EQUATION IS BELOW: (NAVD 1988) + 1.53' = (NGVD 1929)


Always call 811 two full business days before you dig to have underground utilities located and marked.


Sunshine 811.com


SHEET NUMBER C5.00











	TRE	E DISPOSITION						
, , , ,		COMMON NAME	BOTANICAL NAME	DBH	HT	CONDITION	DISPOSITION	MITIGATION
ž		SLASH PINE CARROTWOOD	PINUS ELLIOTTII CUPANIOPSIS ANACARDIOIDES	11.5"		60% INVASIVE	REMAIN REMOVE	NOT REQUIRED
-		SABAL PALM	SABAL PALMETTO		14'	70%	REMAIN	NOT REQUIRED
_		SABAL PALM	SABAL PALMETTO		14'	70%	REMAIN	
	5.	CARROTWOOD	CUPANIOPSIS ANACARDIOIDES			INVASIVE	REMOVE	NOT REQUIRED
_		CARROTWOOD	CUPANIOPSIS ANACARDIOIDES			INVASIVE	REMOVE	NOT REQUIRED
	7.	CARROTWOOD CARROTWOOD	CUPANIOPSIS ANACARDIOIDES CUPANIOPSIS ANACARDIOIDES			INVASIVE INVASIVE	REMOVE REMOVE	NOT REQUIRED NOT REQUIRED
		CARROTWOOD	CUPANIOPSIS ANACARDIOIDES			INVASIVE	REMOVE	NOT REQUIRED
		CARROTWOOD	CUPANIOPSIS ANACARDIOIDES			INVASIVE	REMOVE	NOT REQUIRED
<u></u>	11.	LIVE OAK	QUERCUS VIRGINIANA	8.75"		50%	REMAIN	
3		CARROTWOOD	CUPANIOPSIS ANACARDIOIDES			INVASIVE	REMOVE	NOT REQUIRED
_		LIVE OAK	QUERCUS VIRGINIANA	10.75"		70%	REMAIN	NOT DECUIDED
• •		CARROTWOOD CARROTWOOD	CUPANIOPSIS ANACARDIOIDES CUPANIOPSIS ANACARDIOIDES			INVASIVE INVASIVE	REMOVE REMOVE	NOT REQUIRED NOT REQUIRED
		CARROTWOOD	CUPANIOPSIS ANACARDIOIDES			INVASIVE	REMOVE	NOT REQUIRED
=			QUERCUS VIRGINIANA	11"		60%	REMAIN	
		LIVE OAK	QUERCUS VIRGINIANA	15.5"		70%	REMAIN	
_		LIVE OAK	QUERCUS VIRGINIANA	45"		40%	REMAIN	
1		LIVE OAK	QUERCUS VIRGINIANA	18.5" 6"		50%	REMAIN	
1		DAHOON HOLLY LIVE OAK	ILEX CASSINE QUERCUS VIRGINIANA	6 15.5"		50% 60%	REMAIN REMAIN	
_		LIVE OAK	QUERCUS VIRGINIANA	14"		60%	REMAIN	
_		LIVE OAK	QUERCUS VIRGINIANA	11"		50%	REMAIN	
	25.	LIVE OAK	QUERCUS VIRGINIANA	17"		60%	REMAIN	
Σ = =		LIVE OAK	QUERCUS VIRGINIANA	21"		40%	REMAIN	
$\hat{}$			BUCIDA BUCERAS	27"		30%	REMOVE	TREE FUND
_		WILD TAMARIND	LYSILOMA LATISILIQUUM	14.5"		60%	REMOVE	ON SITE
5		LAUREL OAK WILD TAMARIND	QUERCUS LAURIFOLIA Lysiloma latisiliquum	12.5" 23"		40% 40%	REMOVE REMOVE	TREE FUND TREE FUND
		LIVE OAK	QUERCUS VIRGINIANA	12"		50%	REMAIN	INCL I UND
- - -			QUERCUS VIRGINIANA	. —		50%	REMAIN	
)			QUERCUS VIRGINIANA	13.5"		70%	REMAIN	
V		LIVE OAK	QUERCUS VIRGINIANA	11.5"		70%	REMOVE	ON SITE
_		LIVE OAK	QUERCUS VIRGINIANA	12"		70%	REMOVE	ON SITE
J		LIVE OAK	QUERCUS VIRGINIANA	8"		20%	REMOVE	NOT REQUIRED
Ψ		BLACK OLIVE LIVE OAK		18.5"		60% 60%	REMOVE REMOVE	ON SITE ON SITE
-		LIVE OAK	QUERCUS VIRGINIANA	16.5" 11"		<i>50%</i>	REMOVE	TREE FUND
¬			CARPENTARIA ACUMINATA	11	18'	70%	REMOVE	1 PALM
5			CARPENTARIA ACUMINATA		181	70%		1 PALM
D			CARPENTARIA ACUMINATA		18'	70%		1 PALM
()		SABAL PALM	SABAL PALMETTO		14'	70%	RELOCATE	
		SABAL PALM SABAL PALM	SABAL PALMETTO SABAL PALMETTO		18' 18'	70% 70%	RELOCATE RELOCATE	
_		SABAL PALM	SABAL PALMETTO		18 ¹	70%	RELOCATE	
<u></u>		ROYAL PALM	ROYSTONEA REGIA		20'	80%	RELOCATE	
$\underline{\circ}$		ROYAL PALM	ROYSTONEA REGIA		20'	60%	RELOCATE	
		ROYAL PALM	ROYSTONEA REGIA		25'	70%	RELOCATE	
1		ROYAL PALM	ROYSTONEA REGIA	30"	15'	50%	RELOCATE	
		SILK OAK Laurel oak	GREVILLEA ROBUSTA QUERCUS LAURIFOLIA	24.5"		3 <i>0</i> % 5 <i>0</i> %	REMOVE REMAIN	ON SITE
_		SILK OAK	GREVILLEA ROBUSTA	24.5 14.75"		20%	REMOVE	NOT REQUIRED
J		LIVE OAK	QUERCUS VIRGINIANA	33.5"		70%	REMAIN	
ָט מ	55.	LIVE OAK	QUERCUS VIRGINIANA	11"		20%	REMAIN	
_		LIVE OAK	QUERCUS VIRGINIANA	16"		70%	REMAIN	
D		BLACK OLIVE	BUCIDA BUCERAS	14"		60%	REMAIN	
1)		SILK OAK SABAL PALM	GREVILLEA ROBUSTA SABAL PALMETTO	15"	15'	40% 70%	REMOVE REMOVE	TREE FUND 1 PALM
		LAUREL OAK	QUERCUS LAURIFOLIA	21"	15	50%	REMOVE	ON SITE
>		LAUREL OAK	QUERCUS LAURIFOLIA	13.75"		30%	REMOVE	TREE FUND
- - 5	62.	WILD TAMARIND	LYSILOMA LATISILIQUUM	14"		40%	REMOVE	TREE FUND
		LIVE OAK	QUERCUS VIRGINIANA	15.5"		70%	REMOVE	ON SITE
_		LIVE OAK	QUERCUS VIRGINIANA	10"		50%	REMOVE	ON SITE
1)		WILD TAMARIND Laurel oak	LYSILOMA LATISILIQUUM QUERCUS LAURIFOLIA	18.5" 8"		5 <i>0</i> % 5 <i>0</i> %	REMOVE REMAIN	ON SITE
		LAUREL OAK	QUERCUS LAURIFOLIA	15"		60%	REMAIN	
7		LIVE OAK	QUERCUS VIRGINIANA	9"		50%	REMAIN	
2	69.	BLACK OLIVE	BUCIDA BUCERAS	26 ^{II}		30%	REMAIN	
		LIVE OAK	QUERCUS VIRGINIANA	8.5"		40%	REMAIN	
()		LIVE OAK	QUERCUS VIRGINIANA	9"		40%	REMAIN	
S		LIVE OAK BLACK OLIVE	QUERCUS VIRGINIANA BUCIDA BUCERAS	13" 20.5"		30%	REMAIN REMAIN	
7		SABAL PALM	SABAL PALMETTO	∠0.5	141	60% 70%	REMAIN	
5		SABAL PALM	SABAL PALMETTO		15'	70%	REMAIN	
>		SABAL PALM	SABAL PALMETTO		16'	50%	REMAIN	
<u> </u>		SABAL PALM	SABAL PALMETTO		14'	70%	REMAIN	
ν,		LIVE OAK	QUERCUS VIRGINIANA	20"		70%	REMAIN	
		LIVE OAK	QUERCUS VIRGINIANA	8" 7"		30%	REMAIN	
<u>.</u> .•		LIVE OAK LIVE OAK	QUERCUS VIRGINIANA QUERCUS VIRGINIANA	/" 15"		30% 70%	REMAIN REMAIN	
>		LIVE OAK	QUERCUS VIRGINIANA	8.5"		40%	REMAIN	
• •		LIVE OAK	QUERCUS VIRGINIANA	18"		70%	REMAIN	
<u></u>	84.	WILD TAMARIND	LYSILOMA LATISILIQUUM	19"		50%	REMOVE	ON SITE
		SABAL PALM	SABAL PALMETTO	, .11	16'	70%	RELOCATE	
_		FICUS	FICUS BENJAMINA	44"	17'	20% 70%	REMOVE	NOT REQUIRED
¬		SABAL PALM FICUS	SABAL PALMETTO FICUS BENJAMINA	39"	1 /	70% 10%	RELOCATE REMOVE	NOT REQUIRED
7		WILD TAMARIND	LYSILOMA LATISILIQUUM	13"		40%	REMOVE	TREE FUND
_		WILD TAMARIND	LYSILOMA LATISILIQUUM	25"		60%	REMOVE	ON SITE
Ė	Q1	SABAL PALM	SABAL PALMETTO		15'	70%	RELOCATE	
J	91.		_ , _ , ,		1	70%	DELOCATE	
	92.	SABAL PALM	SABAL PALMETTO		20'		RELOCATE	
	92. 93.	SABAL PALM	SABAL PALMETTO		221	70%	RELOCATE	
משוושה של השפור ה	92. 93. 94.	SABAL PALM SABAL PALM	SABAL PALMETTO SABAL PALMETTO		22' 20'	70% 70%	RELOCATE RELOCATE	
	92. 93. 94. 95.	SABAL PALM	SABAL PALMETTO		221	70%	RELOCATE	

\top	REE FUND INCHES:	
•	TOTAL INCHES REMOVED	447"
	TOTAL INCHES MITIGATED ON SITE	212"
	TOTAL INCHES NOT REQUIRED FOR MITIGATION (CONDITION BELOW 25%)	106"
-	TOTAL TREE FUND INCHES	129"
1	DBH REMOVED 0-8"	64"
]	DBH REMOVED 9-12"	31"
1	DBH REMOVED 13-18"	20"
1	DBH REMOVED 19+"	14"
	TOTAL TREE FUND INCHES	129"

TREE FUND MITIGATION:	
DBH MITIGATION 0-8" 64" @ \$450 = \$28,880	\$28,8 <i>00</i>
DBH MITIGATION 9-12" 31" @ \$650 = \$20,150	\$20,150
DBH MITIGATION 13-18" 20" @ \$850 = \$16,788	\$16,788
DBH MITIGATION 19+" 14" @ \$1000 = \$14,000	\$14,000
TREE FUND MITIGATION REDUCTION (\$79,738 * 50%) = \$39,869 (ALL TREES REQUIRING TREE FUN HAVE CONDITION 50% OR LESS)	-\$39,869 ID MITIGATION
TOTAL TREE FUND MITIGATION	\$39,869


TREE RELOCATION

TREE RELOCATION GENERAL NOTES

- 1. Trees shall be relocated once from their present location to a designated location per the direction of the Project Engineer who shall determine the exact location for each relocated tree and/or palm. Relocation activities will include planting on slopes and/or level grade.
- 2. An ISA Certified Arborist or a Certified Landscape Contractor certified by the Florida Nurserymen and Growers Association shall perform and monitor all tree root pruning and relocation activities.
- 3. Landscape Specifications provided in this construction set shall apply to all relocated trees and/or palms.
- 4. Contractor shall stake and guy all trees at the time of relocation as per details provided in this construction set. Contractor shall be responsible for the maintenance and/or repair of staking and guying during the warranty period. All trees and/or palms shall be braced at least one (1) year or as directed by the Owner's Representative.
- 5. Soil backfill for the installation of trees, palms, shrubs, and ground covers shall be uniform mix of 25% well-rotted compost, 25% topsoil, and 50% clean, weed-free loosened native soil
- 6. Contractor shall submit manufacturers certified analysis for soil amendments to the Owner's
- 7. Contractor shall pay to have the backfill lab tested if requested by the Owner's Representative. Non-soluble wetting agent shall be added to the backfill per the manufacturer's specifications.

1. The Landscape Architect has observed trees that could be impacted by construction of the proposed improvements.

- 2. If construction activities occur within the dripline (or the horizontal extent of the canopy) of a tree, then that tree is a candidate for root pruning.
- 3. Root pruning <u>must</u> occur prior to trenching operations to insure that the roots are cut clean and at proper angles and not mechanically ripped from the earth during construction.
- 4. For trees requiring root pruning, a tree assessment shall be conducted and a root-pruning plan shall be developed by a Certified Arborist or Consulting Arborist. This plan should identify:
- Maximum allowable size of roots to be cut
- Allowable proximity to the trunk for cuts Time of year when root cutting is allowable
- (Note: In Florida, it is best to avoid root pruning during times of the May through September, when the potential for damaging wind loads on trees are greatest.)
- Method for making cuts
- Mitigating canopy pruning
- Type and extent of necessary structural support Schedule for watering/fertilization after pruning
- 5. Implement the root pruning plan per the Arborist's recommendation.



<u>PLAN VIEW</u>

CONNECTION

CORNER

6'H "PERIMETER PLUS" CONSTRUCTION FENCE BY CONWED PLASTICS OR OWNER'S REPRESENTATIVE APPROVED EQUAL. SUBMIT PRODUCT INFORMATION FOR APPROVAL PRIOR TO INSTALLATION.

(2) 8' TALL METAL "T" POSTS OR 2" x 2" X 8' PRESSURE TREATED WOOD POSTS WITH 24" BURIAL BELOW GRADE.

INSTALLATION NOTES:

A. POST SELECTION SHOULD BE BASED ON EXPECTED STRENGTH NEEDS AND THE LENGTH OF TIME FENCE WILL BE IN PLACE. FLEXIBLE FIBERGLASS ROD POSTS ARE RECOMMENDED FOR PARKS, ATHLETIC EVENTS AND CROWD CONTROL INSTALLATIONS. METAL "T" POSTS OR TREATED WOOD POSTS ARE TYPICALLY USED FOR CONSTRUCTION AND OTHER APPLICATIONS.

B. POSTS SHOULD BE DRIVEN INTO THE GROUND TO A DEPTH OF 1/4 OF THE HEIGHT OF THE POST. FOR EXAMPLE, A 8' POST SHOULD BE SET AT LEAST 2' INTO THE

C. SPACE POSTS EVERY 6' (MIN.) TO 8' (MAX.).

D. SECURE FENCING TO POST WITH NYLON CABLE TIES (AVAILABLE FROM CONWED PLASTICS). WOOD STRIPS MAY BE ALSO BE USED TO PROVIDE ADDITIONAL SUPPORT AND PROTECTION BETWEEN TIES AND POSTS.

CONNECTION NOTE: IF WIRE TIES ARE USED, AVOID DIRECT CONTACT Tree/Shrub Protector WITH FENCE. WIRE MAY DAMAGE FENCE OVER TIME.

> PLANS ARE IN NAVD 1988 DATUM CONVERSION EQUATION IS BELOW: (NAVD 1988) + 1.53' = (NGVD 1929)

Always call 811 two full business days before you dig to have underground utilities located and marked.

Sunshine 811.com

OF

HE 386 ey Kimk

RICIA C RICHTER, PLA


D SITION TREE <u></u> DIS

GROUP

DLR

SHEET NUMBER L0.01

THE PRESENCE OF GROUNDWATER SHOULD BE ANTICIPATED. CONTRACTOR'S BID SHALL INCLUDE CONSIDERATION FOR ADDRESSING THIS ISSUE AND OBTAINING ALL NECESSARY PERMITS.



PLANT SC	HEDULE						
TREES BS	BOTANICAL NAME Bursera simaruba 8' CT	<u>COMMON NAME</u> Gumbo Limbo	<u>CONT</u> Cont.	<u>CAL</u> 4" Cal.	<u>SIZE</u> 16' HT x 7' SPR	<u>QTY</u> 23	NATIVE X
LJ	Ligustrum japonicum Min. 5 Stem. 4" Cal.	Ligustrum	Cont.	MULTI	10'HT x 8'SPR	9	
LT	Lagerstroemia indica 'Tuscarora' Min. 5 Stems. 4" Cal. 8' CT	Crape Myrtle	Cont.	MULTI	16' HT x 7' SPR	6	
QV	Quercus virginiana 8' CT	Southern Live Oak	Cont.	5" Cal.	16' HT x 7' SPR	12	X
PALM TREES AC	<u>BOTANICAL NAME</u> Adonidia merrillii Single Trunk.	<u>COMMON NAME</u> Christmas Palm	<u>CONT</u> F.G.	CAL	<u>SIZE</u> 10'-12' OA	<u>QTY</u> 18	<u>NATIVE</u>
RE	Roystonea regia	Royal Palm	F.G.		16' GW	2	×
RR	Roystonea regia	Royal Palm	Relocated			4	×
SR	Sabal palmetto	Cabbage Palm	Relocated			12	X
SS	Sabal palmetto Slick Trunk. Stagger Heights in Groupings	Cabbage Palm	F.G.		20'-28' CT	20	×
VM	Veitchia montgomeryana Double Trunk. Matching Trunks.	Montgomery Palm	F.G.		14'GW	8	
WB	Wodyetia bifurcata	Foxtail Palm	F.G.		12' GW	12	
<u>SHRUBS</u> CA	<u>BOTANICAL NAME</u> Cordyline fruticosa 'Auntie Lou' 3PPP	<u>COMMON NAME</u> 'Auntie Lou' Ti Plant	<u>CONT</u> Cont.	<u>O.C.</u> 24" O.C.	<u>SIZE</u> 24" HT	<u>QTY</u> 34	<u>NATIVE</u>
CR	Chrysobalanus icaco 'Red Tip'	Red Tip Cocopium	Cont.	24" O.C.	24"x24"	457	X
PM	Podocarpus macrophyllus Full to Base.	Podocarpus	Cont.	24" O.C.	36"x24"	454	
PN	Psychotria nervosa	Wild Coffee	Cont.	36" O.C.	24"×24"	52	×
PO	Podocarpus macrophyllus Full to Base.	Podocarpus	Cont.	24" O.C.	72" HT	50	
SHRUB AREAS AV	BOTANICAL NAME Alpinia zerumbet 'Variegata'	<u>COMMON NAME</u> Variegated Shell Ginger	<u>CONT</u> Cont.	<u>0.C.</u> 36"	<u>SIZE</u> 24"x24"	<u>QTY</u> 38	<u>NATIVE</u>
MC	Muhlenbergia capillaris	Pink Muhly	Cont.	36" O.C.	24"×24"	481	X
GROUND COVERS	BOTANICAL NAME Cyrtomium falcatum	<u>COMMON NAME</u> Holly Fern	<u>CONT</u> Cont.	<u>O.C.</u> 24" O.C.	<u>SIZE</u> 15"x15"	<u>QTY</u> 352	<u>NATIVE</u>
FG	Ficus microcarpa 'Green Island'	Green Island Ficus	Cont.	24" O.C.	15"x15"	204	
IV	Ilex vomitoria 'Nana'	'Dwarf' Yaupon Holly	Cont.	18"O.C.	12"x12"	1,002	×
SOD	Stenotaphrum secundatum 'Floratam'	Floratam St. Augustine Sod	sod			± 23,629	sf
SOD2	Paspalum notatum 'Argentine'	'Argentine' Bahia Grass	sod			± 6,828	sf
	BEACH CODE REQUIREMENTS:	PL	ANTING NOT	ES:			

209,978 SF

90,062 SF

27,019 SF

11,460 SF

6,755 SF

7,260 SF

61,939 SF

6,194 SF

9,831 SF

50 TREES

50 TREES

1,163 LF

39 TREES

39 TREES

45 TREES

42 TREES

85 TREES

115 TREES

ANTICIPATED. CONTRACTOR'S BID SHALL

THE PRESENCE OF GROUNDWATER SHOULD BE

INCLUDE CONSIDERATION FOR ADDRESSING THIS

ISSUE AND OBTAINING ALL NECESSARY PERMITS.

C = 209,978 SF - 119,917 SF

D = 90,062 SF * .30

F = 27,019 SF * .25

I = 61,939 * .10

K = 6,194 / 125 SF

N = 1,163 LF / 30

Q = (45 + 39) * .50

OR VEHICULAR USE AREAS:

- CONTRACTOR SHALL REFER TO THE LANDSCAPE PLANTING DETAILS, PLANT LIST, GENERAL NOTES AND ALL CONTRACT DOCUMENTS FOR FURTHER AND COMPLETE INSTRUCTIONS.
- PLANT LIST QUANTITIES ARE PROVIDED FOR CONVENIENCE. IN THE EVENT OF QUANTITY DISCREPANCIES THE DRAWING SHALL TAKE PRECEDENCE. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE LANDSCAPE ARCHITECT PRIOR TO BIDDING.
- PLANT SIZES LISTED ARE THE MINIMUM SIZE THAT WILL BE ACCEPTED FOR THAT PLANT.
- ANY SUBSTITUTION IN SIZE AND/OR PLANT MATERIAL MUST BE APPROVED BY THE LANDSCAPE ARCHITECT IN WRITING. ALL PLANTS WILL BE SUBJECT TO APPROVAL BY LANDSCAPE ARCHITECT AND/OR OWNERS REPRESENTATIVE BEFORE PLANTING CAN BEGIN.
- CONTRACTOR SHALL FIELD ADJUST LOCATION OF PLANT MATERIAL AS NECESSARY TO AVOID DAMAGE TO EXISTING UNDERGROUND UTILITIES AND/OR INTERFERE WITH EXISTING ABOVE GROUND ELEMENTS. ALL CHANGES REQUIRED SHALL BE COMPLETED AT THE CONTRACTOR'S EXPENSE AND SHALL BE COORDINATED WITH THE OWNER'S REPRESENTATIVE AND THE LANDSCAPE ARCHITECT.
- THE CONTRACTOR SHALL BEAR ALL COSTS OF TESTING OF SOILS, AMENDMENTS, ETC. ASSOCIATED WITH THE WORK AND INCLUDED IN THE SPECIFICATIONS.
- CONTRACTOR SHALL FAMILIARIZE HIM/HERSELF WITH THE LIMITS OF WORK AND EXISTING CONDITIONS AND VERIFY ALL INFORMATION. IF DISCREPANCIES EXIST, CONTRACTOR SHALL NOTIFY OWNER'S REPRESENTATIVE IN WRITING WITHIN SEVEN CALENDAR DAYS OF NOTICE TO PROCEED.
- ALL NEW AND TRANSPLANTED PLANT MATERIAL SHALL BE IRRIGATED BY AN AUTOMATIC UNDERGROUND IRRIGATION SYSTEM.

PLANS ARE IN NAVD 1988 DATUM CONVERSION EQUATION IS BELOW: (NAVD 1988) + 1.53' = (NGVD 1929)

have underground utilities located and marked.




Always call 811 two full business days before you dig to

LUB GR

S

SHEET NUMBER L1.00



EXISTING TREE CALCULATION:

NUMBER OF TREES TO BE PRESERVED: 35 TREES NUMBER OF PALMS TO BE PRESERVED: 6 SABAL PALMS @ 3:1 = 2 TREES 2 TREES NUMBER OF PALMS TO BE RELOCATED: 8 TREES 12 SABAL PALMS @ 3:1 = 4 TREES

45 TREES TOTAL NUMBER OF EXISTING TREES:

PROPOSED TREE CALCULATION:

4 ROYAL PALMS @ 1:1 = 4 TREES


45 TREES TOTAL NUMBER OF EXISTING TREES (SEE EXISTING TREE CALCULATIONS) TOTAL NUMBER OF PROPOSED TREES 50 TREES 23 GUMBO LIMBOS 9 LIGUSTRUMS 6 CRAPE MYRTLES 12 LIVE OAKS TOTAL NUMBER OF PROPOSED PALMS 20 TREES 18 CHRISTMAS PALMS @ 3:1 = 6 TREES 2 ROYAL PALMS @ 1:1 = 2 TREES

20 SABAL PALMS @ 3:1 = 6 TREES 8 MONTGOMERY PALMS @ 3:1 = 2 TREES 12 FOXTAIL PALMS @ 3:1 = 4 TREES

70 TREES TOTAL NUMBER OF PROPOSED TREES TOTAL TREES ON SITE 115 TREES

NATIVE TREE CALCULATION: NUMBER OF EXISTING NATIVE TREES TO BE PRESERVED: NUMBER OF EXISTING NATIVE PALMS TO BE PRESERVED: 6 SABAL PALMS @ 3:1 = 2 TREES NUMBER OF EXISTING NATIVE PALMS TO BE RELOCATED: 12 SABAL PALMS @ 3:1 = 4 TREES 4 ROYAL PALMS @ 1:1 = 4 TREES TOTAL NUMBER OF EXISTING NATIVE TREES NUMBER OF PROPOSED NATIVE TREES 23 GUMBO LIMBO = 20 TREES 12 LIVE OAKS = 12 TREES NUMBER OF PROPOSED NATIVE PALMS 2 ROYAL PALMS @ 1:1 = 2 TREES 20 CABBAGE PALMS @ 3:1 = 6 TREES TOTAL NUMBER OF PROPOSED NATIVE TREES TOTAL NUMBER OF NATIVE TREES ON SITE


32 TREES 2 TREES 8 TREES 42 TREES 35 TREES 8 TREES 43 TREES 85 TREES



1. ALL EXISTING SOIL WITHIN LANDSCAPE AREAS ADJACENT TO VEHICULAR USE AREAS IS REQUIRED TO BE REMOVED (TO 30" BELOW GRADE), INSPECTED AND THEN REPLACED WITH A TOPSOIL MIX AS NEEDED IN SPECIFICATION E/LI.II. TOPSOIL MIX SHALL BE SCREENED OF ROCK.


2. ALL PROPERTIES ARE REQUIRED TO HAVE AN OPEN BED INSPECTION PRIOR TO BACKFILLING TO INSURE THE THIRTY (30) INCH DEPTH HAS BEEN MET.

Typical Parking Island Excavation Detail



- ALL ROOT BARRIERS SHALL BE 4' MINIMUM FROM ALL CITY FACILITIES. THE INSTALLATION OF ROOT BARRIERS SHALL BE COORDINATED WITH CITY AND INSPECTED BY CITY PRIOR TO BACKFILLING. ALL ROOT BARRIERS SHALL EXTEND UP TO FINISHED GRADE.
- 3. ROOT BARRIERS SHALL BE MINIMUM 36" DEEP. APPROVED PRODUCTS INCLUDE "DEEP ROOT" AND "ROOT SOLUTIONS". FLEXIBLE BARRIERS SHALL BE 36" PANELS MANUFACTURED BY BIOBARRIER.
- 4. ALL ROOT BARRIERS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS WRITTEN INSTRUCTION.

(B) Typical Tree with Root Barrier



NOTES:

THE PRESENCE OF GROUNDWATER SHOULD BE

INCLUDE CONSIDERATION FOR ADDRESSING THIS ISSUE AND OBTAINING ALL NECESSARY PERMITS.

ANTICIPATED. CONTRACTOR'S BID SHALL

1. THIS DISTANCE SHALL BE 10' MINIMUM FROM ALL CITY FACILITIES IF NO ROOT BARRIER IS USED.

Typical Tree without Root Barrier

PLANS ARE IN NAVD 1988 DATUM CONVERSION EQUATION IS BELOW: (NAVD 1988) + 1.53' = (NGVD 1929)

Always call 811 two full business days before you dig to have underground utilities located and marked.

Sunshine 811.com

SHEET NUMBER L1.01


GROUP,


ANDS


O

P

Kim









CONGRESS STREET RENDERING - DAY



2 CONGRESS STREET RENDERING - NIGHT

LICENSE NUMBER

CONGRESS
DEC.
SCALE A
SCALE A
DESIGNED B
DES

LIER CAR CLUB

SHEET NUMBER

A3.0



I-95 RENDERING - DAY



2 1-95 - NIGHT

I-95 RENDERINGS

COLLIER CAR CLUB

SHEET NUMBER

A3.1

Units	Avg	Max	Min	Avg/Min	Max/Min
Fc	0.1	0.2	0.0	N.A.	N.A.
Fc	0.1	0.2	0.0	N.A.	N.A.
Fc	12.8	14.6	10.3	1.2	1.4
Fc	3.0	7.6	1.0	3.0	7.6
	Fc Fc Fc	Fc 0.1 Fc 0.1 Fc 12.8	Fc 0.1 0.2 Fc 0.1 0.2 Fc 12.8 14.6	Fc 0.1 0.2 0.0 Fc 0.1 0.2 0.0 Fc 12.8 14.6 10.3	Fc 0.1 0.2 0.0 N.A. Fc 0.1 0.2 0.0 N.A. Fc 12.8 14.6 10.3 1.2

Luminaire Schedule Symbol Type

SB2

SD

SR

→ → → → ¬

→ →

0.0 0.0 0.0 0.0 0.0 0.0

0.0 0.0 0.0 0.0 0.0 0.0

0 0 0.0 0.0 0.0 0.0 0.0 0.0

0 0 0.0 0.0 0.0 0.0 0.0 0.0

†0.0 †0.0 †0.0 †0.0 †0.0 †0.0

† · · · · † · · · † · · · † · · · † · · · |

| †o.o †o.o †o.o †o.o †o.o |

| †o.o †o.o †o.o †o.o †o.o |

†o.o †o.o †o.o †o.o †o.o †o.o

0.0 0.0 0.0 0.0 0.0 0.0

0.0 0.0 0.0 0.0 0.0 0.0

- DESIGN FOLLOWS THE ASHRAE/IESNA EXTERIOR LIGHTING STANDARD AND IS IN COMPLIANCE WITH CITY
 - OF DELRAY LIGHTING ORDINANCES.
- 2. ALL LIGHT FIXTURES ARE FULL CUT-OFF TYPE; NO UPLIGHT MAXIMUM MOUNTING HEIGHT IS 25' ABOVE GRADE
- DESIGN MEETS THE MAX. MIN. MAX/MIN. AVERAGE/MIN RATIOS AS DEFINED IN THE LOCAL LIGHTING
- LIGHT SPILLAGE TO ADJOINING PROPERTIES. DESIGN COMPLIES WITH THE REQUIREMENT FOR 0.25 HORIZONTAL AND VERTICAL FOOT-CANDLES MEASURED AT SIX FEET ABOVE GRADE LEVEL ALONG THE

EXISTING BUILDING).1 [†]1.6 [†]2.9 [†]5.9 [†]5.0 [†]3 (5)[†]2 .1 1.4 2.8 5.4 4.7 3 4 2.7 0.0 0.0 0.0 0.0 0.0 0.0 TYP OF (27) 1.6 3.0 5.9 4.9 3.6 4 0.0 0.0 0.0 0.0 0.0 0.0 .1.1.3 3.5 [†]5.9 [†]5.5 [†]3. 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0 0 0 0 0 0 0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 † 0.0 †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 0.0 \(^{\dagger}0.0 \(^{\dagger}0.3 \(^{\dagger}3.1 \(^{\dagger}3.1 \(^{\dagger}3.2 \(^{\dagger}3.2 \(^{\dagger}3.2 \(^{\dagger}3.2 \(^{\dagger}3.3 \(^{\dagger}3.3 \(^{\dagger}3.5 \(^{\dagger}3.5 \(^{\dagger}3.5 \(^{\dagger}3.6 \(^{\dagger}3.6 \(^{\dagger}3.7 \(^{\dagger}3.7 \(^{\dagger}3.8 \(^{\dagger}) \(^{\dagger}3.8 \(^{\dagger}) \(^{\dagger}3.8 \(^{\dagger}) \(^{\dagger}) \(^{\dagger}) \(^{\dagger}) \(^{\dagger}) \(^{\dagger}) \(^{\dagger}) \(^{\dagger} †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 . 1 3 5 6 . 0 6 . 1 4 . 6 2 8 1 . 6 1 2 2 . 2 2 . 4 2 1 2 . 9 3 . 4 3 . 9 4 . 7 4 . to.o to.o to.o to.d \to.o td.o to.o to.o to.o \to.o | | to.o to.o †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 3 3 3 5 . 6 5 5 4 . 2 2 . 7 1 . 6 1 . 7 2 . 6 3 0 3 . 3 3 . 4 4 . 0 4 . 5 5 . 2 5 . 2 5 . †0.0 †0.0 †0.0 †0.0 †0.0 †0.0 0.0 \(^{\dagger}0.0 \(†0.0 †0.0 †0.0 †0.0 †0.0 †0.0 \$\dot{0.0 \dot{0.0 \d †o.o †o.o †o.o †o.o †o.o \$\\ \dots \cdot \c \$\displays{1.6} \frac{1.9}{1.5} \frac{1.6}{1.9} \frac{1.9}{1.5} \frac{1.9}{1.6} \frac{1.9}{1.5} \frac{1.9}{1.6} \frac{1.9}{1.5} \frac{1.9}{1.5} \frac{1.9}{1.5} \frac{1.9}{1.5} \frac{1.9}{1.9} \frac{1.5}{1.5} \frac{1.9}{1.5} \frac{1.9}{1.5 382 4 . 7 5 . 0 43 . 9 4 . 6 2 . 0 2 . 1 4 . 2 2 4 . 2 3 . 9 4 . 2 3 . 9 4 . 2 3 . 9 4 . 2 4 . 2 3 . 9 4 . 0 4 . 2 4 . 2 5 4 . 2 3 . 9 4 . 0 4 . 2 5 4 . 2 3 . 9 5 . 0 5 √\$\.1 \\ 4.6 \\ 5.1 \\ 4.0 \\ 2.6 \\ \1.7 \\ \2.0 \\ 3.3 \\ 3.4 \\ 3.5 \\ 3.2 \\ 2.8 \\ 2.4 \\ 2.2 \\ 8.0 \\ 3.5 \\ 3.4 \\ 3.0 \\ 2.8 \\ 3.5 \\ 3.4 \\ 3.0 \\ 5.8 \\ 1.7 \\ 1.1 \\ 5.7 \\ 0.4 \\ 5.2 \\ 5.1 \\ 5.1 \\ 5.1 \\ 5.1 \\ 5.0

0.4 0.7 \\ \display \quad \frac{1}{1}.1 \\ \frac{1}{2}.4 \\ \display \quad \frac{1}{1}.8 \\ \display \quad \frac{1}{2}.0 \\ \display \quad \frac{1}{2}.1 \\ \display \quad \quad \frac{1}{2}.1 \\ \display \quad \quad \frac{1}{2}.1 \\ \display \quad \qu

| \$\displaystart = 0.0 \displaystart = 0.0 \di

| \$\frac{1}{2}\$ | \$\frac{1}{

*\bar{5}.0\\\dot{0.0\\dot{0.0}\\dot{0.1}\\dot{0.1}\\dot{1.1}\dot{1.1}\\dot{1.1}\dot{1.1}\dot{1.1}\\dot{1.1}\dot

0.0 0.1 \$\frac{1}{2}\frac{1}{4}\frac{1}{3}\frac{1}{3}\frac{1}{4}\frac{1}{3}\frac{1}{3}\frac{1}{4}\f

0.0\0.0 0.1 \0.2\0.\0\\frac{1}{1.2 \cdot 1.7} \frac{1}{1.7} \cdot 1.7 \cdot 1.6 \cdot 1.5 \cdot 1.4 \cdot 4 \cdot \delta 1.6 \cdot 1.9 \cdot 2.3 \cdot 3.3 \cdot 4 \cdot 4.8 \cdot 4.1 \cdot 4.1 \cdot 4.5 \cdot 5.5 \cdot 5.1 \cdot 4.8 \cdot 3 \cdot 3 \cdot 2.6 \cdot 1.7 \cdot 1.0 \cdot 0.6 \cdot 0.3 \cdot 0.2 \cdot 0.1 \cdot 0.0 \cdot 0

4.1 56 2 2.7 2.0 1.9 1.9 2.1 3.1 4.2 4.3 3.7 2.9 2.5 2.2 2.0 1.9 1 6 0.8 0.6 0.4 0.3 0.2 0.1 0.1 0.0 0.0 0.0 0.0 0.0

TYP OF (6)

0.0 0.1 2.0 3.6 5.4 4.6 3.1 2.0 2/.3

to. 6 to. 1 1.7 3.2 to 8 to 6 to 14 to 18 to 15 to 15

1.8/3.1/5.2 ⁴.6 ³ 2

5.8 4.8 3.2

1 21.7 2.8 6.0 4.9 3 25

†0.0 †\1°\1.1 †2.\4.4.1 †4.3 †3.5 †2.\\2\1

NOT FOR CONSTRUCTION 02-14-2019

39-18810-00 **PHOTOMETRIC** PLAN

† . o † . o † . o †

to.o to.o to.o to.

to. 0 to. 0 to. 0

†0.0 †0.0 †0.0 †0.0 †d

, †o.o †o.o †o.o †o.o †o.\\

೨\\to.o to.o to.o to.o to.o\\

10.0 10.0 10.0 10.0 10.0 1

\do.o \do.o do.o do.o d\o

to.o to.o|\to.o|\to.o to.o to.o to.o| to.|\to.|oto.o

to.o to.o \\\to.o to.o to.o to.o to.o \\\\\p\|\p\|

\$\forall \dagger \dagg

to.o to.o to.bl/ to.o to.l/o to.o to.o to.o \to.l/o

\$\doldright\rangle \doldright\rangle \doldright\

†0.0 †0.0 †0.0 | tbl.0 †0.0|| | †0.0 †0.0 †0.0 †0.0 |

\$\dagger{\partial} \begin{aligned}
\dagger{\partial} \dagger{\part

\$\dagger{0.0} \dagger{0.0} \dag

| to.o to.o to.e_{r1}to.o|to||o to||o to.o to.o to.o to.o||to||to||1

\$ 0.0 \$ 0.0

\$\dagger{0.0 \dagger{0.0 \dagg

\$\frac{1}{0.0} \frac{1}{0.0} \

\$\frac{1}{2}\cdot 0.0 \quad \frac{1}{2}\cdot 0.0 \quad \quad \frac{1}{2}\cdot 0.0 \quad \quad 0.0 \quad \quad 0.0 \quad 0.0 \quad \quad 0.0 \quad 0.0

| to.o to.o to.o to.o | to.| p to| o to.o to.o to.o | | to|

\$\dagger_0.0 \dagger_0.0 \dagg

DLR Group | STAFFELBACH

PHOTOMETRIC RENDERING