THIS DOCUMENT IS THE PROPERTY OF CURRIE SOWARDS AGUILA ARCHITECTS INC., ALL RIGHTS ARE RESERVED. ANY POSSESSION, REPRODUCTION OR OTHER USE OF THIS DOCUMENT, WITHOUT THE WRITTEN CONSENT OF CURRIE SOWARDS AGUILA ARCHITECTS INC., IS PROHIBITED.

Submitting Agency: SESCO LIGHTING
Description: 4DR-TL-L20-840-DIM-UNV/O-W-OF-CS-MWT-WET /CC/N-F1
Project: HAMPTON DELRAY - #19-1570
Type: H

4DR LED 4.5" Downlight – Round

Williams

NEW CONSTRUCTION AND REMODEL



CATALOG #:
TYPE:
PROJECT:

FEATURES

TrimLock™
- Innovative TrimLock reflector retention system allows trim to remain flush with ceiling plane
- Die cast trim choices include flush, reveal and square
- Industry-leading efficacies as high as 110 lm/W – ENERGY STAR® certified
- Wet location and IC rated available
- Available on Quickship

SPECIFICATIONS
- HOUSING – Die-cast aluminum trim ring and housing with integral heat sink. Galvanized steel splice compartment with driver mounting polycarbonate/steel hybrid plate. Housing depth including thickness from 12" – 1.75" (See options for optional extended housing).
- TRIMLOK – Innovative TrimLock reflector retention system allows trim to remain flush with the ceiling plane.
- OPEN REFLECTOR – Low-reflected specular aluminum. Clear semi-specular finish standard.
- LENSED TRIM – Die-cast aluminum frame with 1/8" thick acrylic lens (opal or clear).
- ELECTRICAL – High-performance Class 2 C.O.B. LED array. Modular quick-connect design allows for easy replacement of light assembly to driver. Reported LM-80 data hours. Reported LM-80 data hours. Reported LM-80 data hours.
- MOUNTING – Recessed. 20 ga galvanized steel mounting pan for new construction or non-accessible ceiling applications. Includes recessed bracket hardware. Minimum 24" O.C. standard spacing. Compatible with most LED and LED lamps packages.
- LISTINGS – Listed to conforms to UL 1598. Certified to CANCSA C22.2 No. 250.0 for damp locations. Suitable for use in Title 24 CA, JA8-2016 for remote installation.
- Qualified to meet California Energy Commission ceiling when specified with WET/CC or TD options.
- Qualified ENERGY STAR® certified in select configurations, see www.energystar.gov
- IC-rated for direct contact with insulation when specified with CC option.
- City of Chicago Environmental Air approved when specified with CP option.
- Meets Buy American EO14005 when specified with DFA option.
- RoHS compliant.
- Refer to Sesco's 5 year limited warranty, see Sesco.com/warranty.

ORDERING EXAMPLE: 4DR - TL - L20/835 - OPTIONS - DIM - UNV/ - CNF - OF - CS - TRIM OPTIONS - W - F1

HOUSING / TRIM / MOUNT

HOUSING

SERIES	LUMENS [1]	CRI	CCT	OPTIONS	DRIVER [2]	VOLTAGE
4DR Downlight	L20 1,000lm L30 1,500lm L40 2,500lm L50 3,500lm L60 4,500lm L80 6,000lm	8 80 CRI 9 90 CRI	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K	SCA_____ AFA CP DFA EM/10W EM/7W/20W CP NL TC	Shipped ballast Shipped Hot Airtight construction Canada 10 watt emergency battery [4] 10 watt emergency battery with integral test switch [4] Chicago plenum (ECEA) [6] Damp location Adjustable mounting arm (no 1/2" – 2-1/4" thick ceilings	120 120V 208 208V 277 277V 347 347V 480 480V UNV 120-277V

TRIM

TRIM TYPE	DISTRIBUTION [10]	FLANGE TYPE	REFLECTOR FINISH	TRIM OPTIONS
Specular Clear Specular Clear with Glass Lens (recessed mounting) Specular White Specular Black Specular Gold Specular Bronze Specular Natural Aluminum Specular Nickel Specular Chrome Specular Copper Specular Champagne Specular Stainless Specular Black Nickel Specular Antique Bronze Specular Gun Metal Specular Satin Chrome Specular Satin Nickel Specular Satin Aluminum Specular Satin Copper Specular Satin Bronze Specular Satin Stainless Specular Satin Black Nickel Specular Satin Antique Bronze Specular Satin Gun Metal Specular Satin Champagne Specular Satin Gold Specular Satin Natural